


Product Information		Lepro LE	
Product conformity acc. to	:	Ecodesign requirements	
Supplier's name or trade mark	:	Lepro, LE	
Supplier's address	:	LE Innovation Limited One Spencer Dock, North Wall Quay, Dublin 1, D01 X9R7,	
Model identifier	:	350033-DW-EU	
Model identifier of all equivalent models	:	350033-DW-EU	
With separate control gear	:	no	
Type of light source			
Lighting technology used	:	LED	Non-directional or directional
Mains or non-mains	:	MLS	Connected light source (CLS)
Colour-tuneable light source	:	no	Envelope
High luminance light source	:	no	Anti-glare shield
Dimmable	:	no	
General product parameters			
Energy consumption in on-mode (kWh/1000h)	:	200.0	Energy efficiency class
Useful luminous flux, indicating if it refers to the flux in a sphere, in a wide cone or in a narrow cone (lm)	:	28000	in sphere
On-mode power (Pon), expressed in W	:	200.0	Standby power (Psb) expressed in W and rounded to the second decimal
Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal	:	-	Colour rendering index, rounded to the nearest integer, or the range of CRI values that can be set
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts if any (mm)	Height	346	Spectral power distribution in the range 250nm to 800 nm at full-load
	Width	346	
	Depth	122	
Claim of equivalent power	:	-	If yes, equivalent power (W)
			Chromaticity coordinates (x and y)
Parameters for directional light sources			
Peak luminous intensity (cd)	:	7200	Beam angle in degrees, or the range of beam angles that can be set
Parameters for LED and OLED light sources			
R9 colour rendering index value	:	10	Survival factor
the lumen maintenance factor	:	0.98	
Parameters for LED and OLED mains light sources			
displacement factor	:	0.9	Colour consistency in McAdam ellipses
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	:	-	If yes then replacement claim (W)
Flicker metric (Pst LM)	:	0.21	Stroboscopic effect metric (SVM)



Declared/Measured values				
Voltage (V)	:	230AC		Useful luminous flux (lm) : 28000 in sphere
Frequency (Hz)	:	50		Luminance-HLLS (cd/mm²) : 7200 HLLS
On-mode power P _{on} (W)	:	200		Beam angle (°) : 110 DLS
Standby power P _{sb} (W)	:	0.05		Networked standby power P _{net} (W) : - CLS
Displacement factor	:	0.95		CCT(K) : 5000
Colour consistency (SDCM)	:	6		CRI : 80
Flicker metric P _{stLM}	:	0.21		Stroboscopic effect metric SVM : 0.1
P _{onmax} (W)	:	339.2		excitation purity for Blue 440nm-490nm : - CTLS
Total mains efficacy (lm/W)	:	164.6		excitation purity for Green 520nm-570nm : - CTLS
LB0750(H)	:	50000		excitation purity for Red 610nm-670nm : - CTLS
Parameters for separate control gear				
Voltage (V)	:	-		Maximum output power (W) : -
No-load power P _{no} (W)	:	-		Efficiency in full load (%) : -
Standby power P _{sb} (W)	:	-		Networked standby power P _{net} (W) : -
the type of light sources for which it is intended	:	NMLS	LED	compatible dimmable light sources : only the together light source
Outer dimensions (mm)	Hight	-		mass(g) : -
	Width	-		
	Depth	-		
$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM (lm/W)=164.2 lm/W$ 160 ≤ η_{TM} < 185 energy efficiency class correspond to C				
Energy efficiency and functional requirements				
Classification acc. To 2019/2020	<input checked="" type="checkbox"/>	Directional lamp	<input type="checkbox"/>	Non directional lamp
Compliance:	<input checked="" type="checkbox"/>	Yes	<input type="checkbox"/>	No
Measurement conditions				
Standards	:	EU 2019/2015, EU 2019/2020		
Tolerances	:	according to ErP regulation		
Measurement setup	:	4P, SSL port, 1.5m sphere		
Voltage (V)	:	declared voltage		
Burning position	:	Base up		
Ambient temperature:	:	25°C +/- 2K		
Burn in	:	1h		
Total operating time during measurement	:	15min		
Non standard stability criteria	:	Luminous flux tolerance 0.5% within 60 sec.		
Uncertainties	:	according to JCGM (GUM) and CIE 198		
Important notes / WARNINGS:				
The product needs to be powered off before install; Please see users' instruction				
Signature	:	Vick Xun		