


Product Information		Lepro   LE	
Product conformity acc. to	:	Ecodesign requirements	
Supplier's name or trade mark	:	Lepro, LE	
Supplier's address	:	One Spencer Dock, North Wall Quay, Dublin 1, D01 X9R7, Ireland	
Model identifier	:	EAN310004-DWW-EU	
Model identifier of all equivalent models	:		
With separate control gear	:	yes	
<b>Type of light source</b>			
Lighting technology used	:	LED	Non-directional or directional
Mains or non-mains	:	NMLS	Connected light source (CLS)
Colour-tunable light source	:	no	Envelope
High luminance light source	:	no	Anti-glare shield
Dimmable	:	yes	
<b>General product parameters</b>			
Energy consumption in on-mode (kWh/1000h)	:	7.0	Energy efficiency class
Useful luminous flux, indicating if it refers to the flux in a sphere, in a wide cone or in a narrow cone (lm)	:	655	Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set
On-mode power (Pon), expressed in W	:	7.0	Standby power (Psb) expressed in W and rounded to the second decimal
Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal	:	-	Colour rendering index, rounded to the nearest integer, or the range of CRI values that can be set
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts if any (mm)	Height	39.5	Spectral power distribution in the range 250nm to 800 nm at full-load
	Width	100	
	Depth	403	
Claim of equivalent power	:	-	If yes, equivalent power (W)
			Chromaticity coordinates (x and y)
			0.322, 0.331
<b>Parameters for directional light sources</b>			
Peak luminous intensity (cd)	:	-	Beam angle in degrees, or the range of beam angles that can be set
<b>Parameters for LED and OLED light sources</b>			
R9 colour rendering index value	:	15	Survival factor
the lumen maintenance factor	:	0.92	
<b>Parameters for LED and OLED mains light sources</b>			
displacement factor	:	-	Colour consistency in McAdam ellipses
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	:	-	If yes then replacement claim (W)
Flicker metric (Pst LM)	:	1	Stroboscopic effect metric (SVM)
			0.4



Declared/Measured values			
Voltage (V)	:	12	Useful luminous flux (lm) : 655 in sphere
Frequency (Hz)	:	DC	Luminance-HLLS (cd/mm²) : - HLLS
On-mode power P <sub>on</sub> (W)	:	7	Beam angle (°) : - DLS
Standby power P <sub>sb</sub> (W)	:	0.4	Networked standby power P <sub>net</sub> (W) : - CLS
Displacement factor	:	-	CCT(K) : 6000
Colour consistency (SDCM)	:	6	CRI : 80
Flicker metric P <sub>stLM</sub>	:	0.3	Stroboscopic effect metric SVM : 0.002
P <sub>onmax</sub> (W)	:	7	excitation purity for Blue 440nm-490nm : - CTLS
Total mains efficacy (lm/W)	:	86.64	excitation purity for Green 520nm-570nm : - CTLS
LB0750(H)	:	15000	excitation purity for Red 610nm-670nm : - CTLS
Parameters for separate control gear			
Voltage (V)	:	100-240	Maximum output power (W) : 12
No-load power P <sub>no</sub> (W)	:	0.1	Efficiency in full load (%) : 81
Standby power P <sub>sb</sub> (W)	:	0.5	Networked standby power P <sub>net</sub> (W) : 0.4
the type of light sources for which it is intended	:	NMLS	LED compatible dimmable light sources : only the together light source
Outer dimensions (mm)	Height	54	mass(g) : 80
	Width	36	
	Depth	250	
$\eta_{TM} = (\Phi_{use}/P_{on}) \times FTM \text{ (lm/W)} = 86.64 \text{ lm/W}$ $85 \leq \eta_{TM} < 110$ energy efficiency class correspond to F			
Energy efficiency and functional requirements			
Classification acc. To 2019/2020		Directional lamp	<input checked="" type="checkbox"/> Non directional lamp
Compliance:	<input checked="" type="checkbox"/>	Yes	<input type="checkbox"/> No
Measurement conditions			
Standards	:	EU 2019/2015, EU 2019/2020	
Tolerances	:	according to ErP regulation	
Measurement setup	:	4P, SSL port, 1.5m sphere	
Voltage (V)	:	declared voltage	
Burning position	:	Base up	
Ambient temperature:	:	25°C +/- 2K	
Burn in	:	1h	
Total operating time during measurement	:	15min	
Non standard stability criteria	:	Luminous flux tolerance 0.5% within 60 sec.	
Uncertainties	:	according to JCGM (GUM) and CIE 198	
Important notes / WARNINGS:			
1、 This product contains replaceable light sources and separated control gears. The replaceable shall be the same model no. and brands.			
2、 Separate the light source and control gears from the containing products at the end of life.			
<b>The product needs to be powered off before install; Please see users' instruction</b>			
Signature	:	Vick Xun	