

Product Information


Lepro | LE

Product conformity acc. to	:	Ecodesign requirements
Supplier's name or trade mark	:	Lepro
Supplier's address	:	One Spencer Dock, North Wall Quay, Dublin 1, D01 X9R7, Ireland
Model identifier	:	PR1500024-WW-EU
Model identifier of all equivalent models	:	-
With separate control gear	:	no

Type of light source

Lighting technology used	:	LED	Non-directional or directional	:	NDLS
Mains or non-mains	:	MLS	Connected light source(CLS)	:	no
Colour-tunable light source	:	no	Envelope	:	non-clear
High luminance light source	:	no	Anti-glare shield	:	no
Dimmable	:	no			

General product parameters

Energy consumption in on-mode(kWh/1000h)	:	15.0	Energy efficiency class	:	F
Useful luminous flux, indicating if it refers to the flux in a sphere, in a wide cone or in a narrow cone (lm)	:	1450	in sphere	Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures,rounded to the nearest 100K, that can be set	3000
On-mode power(Pon),expressed in W	:	15.0		Standby power (Psb) expressed in W and rounded to the second decimal	0.00
Networked standby power(Pnet) for CLS, expressed in W and rounded to the second decimal	:	0.00		Colour rendering index, rounded to the nearest integer, or the range of CRI values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts if any(mm)	Hight	48		Spectral power distribution in the range 250nm to 800 nm at full-load	
	Width	220			
	Depth	220			
Claim of equivalent power	:	-		If yes, equivalent power (W)	-
				Chromaticity coordinates (x and y)	0.440,0.403

Parameters for directional light sources

Peak luminous intensity (cd)	:	-	Beam angle in degrees, or the range of beam angles that can be set	:	-
------------------------------	---	---	--	---	---

Parameters for LED and OLED light sources

R9 colour rendering index value	:	10	Survival factor	:	1.00
the lumen maintenance factor	:	0.96			

Parameters for LED and OLED mains light sources

displacement factor	:	0.95	Colour consistency in McAdam ellipses	:	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	:	-	If yes then replacement claim W)	:	-
Flicker metric (Pst LM)	:	0.2	Stroboscopic effect metric (SVM)	:	0.1

Declared/Measured values						
Voltage (V) : 230		Useful luminous flux (lm) : 1450	in sphere			
Frequency (Hz) : 50		Luminance-HLLS (cd/mm ²) : -	HLLS			
On-mode power Pon (W) : 15.0		Beam angle (°) : -	DLS			
Standby power Psb (W) : 0.00		Networked standby power Pnet (W) : 0.00	CLS			
Displacement factor : 0.95		CCT(K) : 3000				
Colour consistency (SDCM) : 6		CRI : 80				
Flicker metric PstLM : 0.2		Stroboscopic effect metric SVM : 0.1				
Ponmax (W) : 15.1		excitation purity for Blue 440nm-490nm : -	CTLS			
Total mains efficacy (lm/W) : 100		excitation purity for Green 520nm-570nm : -	CTLS			
LB0750(H) : 15000		excitation purity for Red 610nm-670nm : -	CTLS			
Parameters for separate control gear						
Voltage (V) : -		Maximum output power (W) : -				
No-load power Pno (W) : -		Efficiency in full load (%) : -				
Standby power Psb (W) : -		Networked standby power Pnet (W) : -				
the type of light sources for which it is intended : -		compatible dimmable light sources : -				
Outer dimensions (mm)	Height : - Width : - Depth : -	mass(g) : -				
$\eta_{TM} = (\Phi_{use}/Pon) \times FTM \text{ (lm/W)} = 100 \text{ lm/W}$ $85 \leq \eta_{TM} < 110$ energy efficiency class correspond to F						
Energy efficiency and functional requirements						
Classification acc. To 2019/2020	<input checked="" type="checkbox"/>	Directional lamp	<input checked="" type="checkbox"/> Non directional lamp			
Compliance:	<input checked="" type="checkbox"/> Yes		<input checked="" type="checkbox"/> No			
Measurement conditions						
Standards	EU 2019/2015, EU 2019/2020					
Tolerances	according to ErP regulation					
Measurement setup	4P, SSL port, 1.5m sphere					
Voltage (V)	declared voltage					
Burning position	Base up					
Ambient temperature:	25°C +/- 2K					
Burn in	1h					
Total operating time during measurement	15min					
Non standard stability criteria	Luminous flux tolerance 0.5% within 60 sec.					
Uncertainties	according to JCGM (GUM) and CIE 198					
Important notes / WARNINGS:						
The product needs to be powered off before install; Please see users' instruction						
Signature	Vick Xun					